

Acciai Speciali Terni S.p.A. con Unico Socio

Sistema di Gestione per la Qualità

DECLARATION OF PERFORMANCE N° 0009

In compliance with Regulation 305/11 of the European Parliament and of the Council of 9 st march 2011 laying down harmonized conditions for the marketing of construction products and repealing Council Directive 89/106/CE and Regulation 574/14 amending Annex III the above mentioned Regulation

Unique identification code of the product	Steel grade 1.4401 manufactured in accordance with UNI EN 10088-4 in hot rolled plates coils or sheets or cold rolled coils or sheets				
Intended uses	to be used as construction product				
Manufacturer	Acciai Speciali Terni V.le Brin 218 - 05100 Terni Italia				
System of AVCP	2+				
Notified body	Notified body n°2592, Qoncert Stradone Farnese, 39G - 29121 Piacenza (Italia)				
Harmonised standard	UNI EN 10088-4				

Dop 0009 Rev. 3 Data: 07.12.2018 Pagina 1 di 2



Acciai Speciali Terni S.p.A. con Unico Socio

	Decla	red perfor	mance	s for 1	1.4401 ste	eel grade		
Essential characteristic	Performance						Harmonised technical specification	
Tolerance on dimensions and thickness		according to the			order			
Yield strenght (0.2%)	plat hot rolle		≥220	(tra	nsv.)	МРа	EN 10088/4	
	cold roll	ed coils	≥240	(tra	nsv.)	MPa		
Yield strenght (1%)	plat hot rolle		≥260	(tra	nsv.)	MPa	EN 10088/4	
	cold roll	ed coils	≥270	(tra	nsv.)	MPa		
Tensile strenght	plates		≥520 and ≤670		≤670	MPa	EN 10088/4	
	hot rolled coils		≥530 and ≤680		≤680	MPa		
Impact energy (J)	plates		thick.≤50mm		100 (long)			
					60 (tr)			
	hot rolled coils		thick.≤6.5mm		mm	NPD	EN 10088/4	
	cold rolled coils		thick.≤5.0mm		mm	NPD		
Elongation	plates		≥45	(long ÷ transv)		%	EN 10088/4	
	hot rolled coils		≥40	(long ÷ transv)		%		
	cold rolled coils		≥40	(long ÷ transv)		%		
Resistence to intergranular corrosion	in the delivery condition yes					EN 10088/4		
	in the sensitized condition no							
Durability (chemical composition%)	C ≤ 0.07	Mn ≤ 2.00	S ≤ (0.015	16.5 ≤ Cı ≤ 18.5		EN 40000/4	
	Si ≤ 1.00	P ≤ 0.045	N≤	0.10	2.0 ≤ Mo ≤ 2.5		EN 10088/4	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) N°305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf on the manufacturer by:

Paolo Zanella

Terni on 07/12/2018

Quality Assurance Responsible Acciai Speciali

Dop 0009 Rev. 3 Data: **07.12.2018** Pagina **2** di **2**