

DICHIARAZIONE DI PRESTAZIONE N° 0016

In ottemperanza al Regolamento 305/11 del Parlamento Europeo e del Consiglio della Comunità Europea del 9 marzo 2011 che fissa condizioni armonizzate per la commercializzazione dei prodotti da costruzione e abroga la direttiva 89/106/CE del Consiglio e in ottemperanza al Regolamento 574/14 che modifica l'allegato III del suddetto regolamento

Codice di identificazione unico del prodotto	Acciaio 1.4513 prodotto secondo UNI EN 10088-4 in nastri o fogli laminati a freddo
Usi previsti	utilizzabile come prodotto da costruzione o ingegneria civile
Fabbricante	Acciai Speciali Terni V.le Brin 218 - 05100 Terni Italia
Sistemi di VVCP	2+
Organismi notificati	Organismo Notificato n°2592 Qoncert Stradone Farnese 39G Piacenza (Italia)
Norma armonizzata	UNI EN 10088-4

Sistema di Gestione per la Qualità

		PRESTAZIONI DICHIARATE Acciaio 1.4513				
Caratteristica essenziale		Prestazione				Norma armonizzata
tolleranze dimensionali e di spessore			secondo ordine			
carico di snervamento (0.2%)	nastri a freddo	≥200	long.	MPa	EN 10088/4	
		≥220	trasv.	MPa		
carico di rottura	nastri a freddo	≥400 e ≤550			MPa	EN 10088/4
allungamento a rottura	nastri a freddo	≥23	(long ÷ trasv)	%	EN 10088/4	
resistenza a corrosione intergranulare	in condizioni di fornitura				si	EN 10088/4
	in condizioni di sensibilizzazione				si	
Composizione chimica %	C ≤ 0.025	S ≤ 0.015	16.0 ≤ Cr ≤ 18.0		EN 10088/4	
	Si ≤ 1.00	P ≤ 0.040	0.80 ≤ Mo ≤ 1.40			
	Mn ≤ 1.00	N ≤ 0.020	0.30 ≤ Ti ≤ 0.60			

La prestazione del prodotto sopra identificato è conforme all'insieme delle prestazioni dichiarate. La presente dichiarazione di responsabilità viene emessa, in conformità al regolamento (UE) n. 305/2011, sotto la sola responsabilità del fabbricante sopra indicato.

DECLARATION OF PERFORMANCE N° 0016

In compliance with Regulation 305/11 of the European Parliament and of the Council of 9st march 2011 laying down harmonized conditions for the marketing of construction products and repealing Council Directive 89/106/CE and in compliance with Regulation 574/14 amending Annex III of the above mentioned Regulation

Unique identification code of the product	Steel grade 1.4513 manufactured in accordance with UNI EN 10088-4 in cold rolled coils or sheets
Intended uses	to be used as construction product
Manufacturer	Acciai Speciali Terni V.le Brin 218 - 05100 Terni Italia
System of AVCP	2+
Notified body	Notified body n°2592, Qoncert Stradone Farnese, 39G - 29121 Piacenza (Italia)
Harmonised standard	UNI EN 10088-4


Sistema di Gestione per la Qualità

		Declared performances for 1.4513 steel grade				
Essential characteristic	Performance				Harmonised technical specification	
Tolerance on dimensions and thickness		according to the order				
Yield strenght (0.2%)	cold rolled coils	≥200	long.	MPa	EN 10088/4	
		≥220	transv.	MPa		
Tensile strenght	cold rolled coils	≥400 and ≤550		MPa	EN 10088/4	
Elongation	cold rolled coils	≥23	(long ÷ transv)	%	EN 10088/4	
Resistance to intergranular corrosion	in the delivery condition			yes	EN 10088/4	
	in the sensitized condition			yes		
Durability (chemical composition%)	C ≤ 0.025	N ≤ 0.020		16.0 ≤ Cr ≤ 18.0	EN 10088/4	
	Si ≤ 1.00	S ≤ 0.015		0.80 ≤ Mo ≤ 1.40		
	Mn ≤ 1.00	P ≤ 0.040		0.30 ≤ Ti ≤ 0.60		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) N°305/2011, under the sole responsibility of the manufacturer identified above.

Firmato a nome e conto del fabbricante da:
Signed for and on behalf on the manufacturer by:

Ing. Gian Luca Gigli
 Chief Technical Officer
 Acciai Speciali Terni



Terni, 02/09/2026